



350 Cambridge Ave, Suite 250
Palo Alto, CA 94306-1550
TEL 650.330.2310
FAX 650.330.7314

FACSIMILE COVER SHEET

DATE:

July 31, 2006

FILE NO:

APPM/006303/CPI/COPPER/PJS

TO:

USPTO

FAX NO:

(571) 273-8300

COMPANY:

Patterson and Sheridan LLP

FROM:

Ya-Fen Chen

PAGE(S) with cover:

31

ORIGINAL TO

FOLLOW?

☐ YES ☒ NO

APPEAL BRIEF

TITLE:

INTEGRATION OF BARRIER LAYER AND SEED LAYER

U.S. SERIAL NO.:

09/965,370

FILING DATE:

September 26, 2001

INVENTOR:

CHUNG, et al.

EXAMINER:

Eric B. Fuller

GROUP ART UNIT:

1762

CONFIRMATION NO.:

6507

MESSAGE:

2 coples of Fee Transmittal

CONFIDENTIALITY NOTE

The document accompanying this facsimile transmission contains information from the law firm of Patterson & Sheridan, L.L.P. which is confidential or privileged. The information is intended to be for the use of the individual or entity named on this transmission sheet. If you are not the intended recipient, be aware that any disclosure, copying, distribution or use of the contents of this faxed information is prohibited. If you have received this facsimile in error, please notify us by telephone immediately so that we can arrange for the retrieval of the original documents at no cost to you.

489273_1

RECEIVED

07/31/2005 10:30 4005636492

PATENT

CENTRAL FAX CENTER

PAGE 02/03

JUL 3 1 2006 PTO/SB/17 (01-08)
Approved for use though 07/31/2006, OMB 0951-0092
U.S. Patent and Tradement Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction	on April of 1	995, no pareons are required	Parageon of	e e collection e	Peetru nothumothi	R displays	a valid OMB	control number.		
No. of the last of		inflores April 2005 (H.R. 4818).			Complete H	Кложп				
FEE TRANSMITTAL			Applicatio	n Number	09/965,370					
			Filing Del		September 26, 2001					
for F	FY 2	006	First Nam	rad (nywydor	Hus CHUNG	. — . — .				
Applicant claims small	mtily st	tus. See 37 CFR 1.27	Examine	Name	Eric 9. Puller					
			Art UMR		1762					
TOTAL AMOUNT OF PAY	MENT	(\$) 500.00	Attorney	Docket No.	APPW008365/GPIA	COPPERVE	18			
METHOD OF PAYMENT	(check	all that apply)								
☐ Check ☐ Credit Ca	rd 🗖	Money Order 🔲 Nani	e 🗆 Oth	er (pleasa id	lent <u>ify) :</u>					
57 Deposit Account Day	ost Am	ount Number: <u>60-1074/API</u>	<u>PM/006308</u>	<u>rww</u> Depos	it Account Nema:	Applied I	Materials			
For the above-lder	utified de	posit secount, the Director	la horeby a	uthorized to: (ouscal in that abb	לעו				
For the above-identified deposit account, the Director is hereby authorized to: (otheck all that apply) Charge fee(s) indicated below. except for the filling tee										
Charge any additional fee(a) or underpayments of fee(a) Cradit any overpayments										
Under 37 C Under 37 C WARNING: Information on this							de crodit car	.a.		
WARNING: Information on this Information and authorization	i form 162 2-OTA no	y pecome public, Gradit dan 1939.	o itagamento	A STANK INC D	·					
FEE CALCULATION										
1. BASIC FILING, SEA	RCH. A	ND EXAMINATION FE	E\$							
1. DASIC FIELDS	FILING	FEES	SPAKCH!	FEES	EXAMINA					
_		Small Entity	Fee(\$1)	Small Entit	<u>/</u> Fee(\$)	Smail Er Fee(S		es Pald (\$)		
Application Type	Fee (\$		500	250	200	100	-			
Littity	300 200		100	50	130	65	_	·		
Design	200		300	15D	160	80				
Plant	300	100	500	250	600	300	-			
Refesue Provisional	200	100	0	٥	0	0				
2. EXCESS CLAIM FE	•						<u>S</u> m:	ILL Entity		
Pee Description						Fee	- 11	Fee (\$)		
Fach daim over 20 (Including Refssues)								25		
Each independent dia	dm ovel	3 (including Relasues)					200 100 380 180			
Mutitple dependent claims Yota Claims Extra Claims Fee(\$)			Fee	Fee Paid (\$)				fulfiple Department Claims		
-20 or HP	_	×				E	ee (\$)	Fee Paid (3)		
		6 paid for. If greater then 20,				_				
Indep. Cisima	Extr	Claims Fee(\$)	Fee	Pald (\$)						
- 3 of HP		_ x	= _							
		and claims paid for, if greater t	160 Z.							
3. APPLICATION SIZE	FEE	1.400 L ata a		uali idaa ala	-teasioniku filad s		a or combi	ifer		
If the specification and	drawn	ga exceed 100 sheets of 1,52(e)), the application	n elze fee d	xçıbanı ele İva bi 8250 (\$125 for email 6	entity) for	each add	itional 50		
ijstinga under d	ion then		מרוב ווווון וווווו	0 37 CPK 1.	10131					
Total Sheets	Extra	Sheets Number of	esch add	utiolităi pri o	r marnon mere	of Fee	- (B) E9	Paid (\$)		
-100	-		(Lonnq mb	to a whole i	number) x		_ [- D-14 (2)		
4. OTHER FEE(9)										
Non-English Specification, \$130 fee (no small entity discount)										
Other (e.g., lat	te filing s	aurcharge <u>)</u> : 14 <u>02/2402</u> -	- Appeal Br	<u> </u>						
SUBMITTED BY	7	AG (John A)	1	(togleys)on No.						
Staresture	1	V W Makedy	gran.	(Attorney/Agent			Talaphone	(713) 823-858		
Alama (Petril/Type) Ro	bert W.	Mulcahy					Date	July 31, 2008		
Name (Print/Type) R6 This collection of information is requ	red by 57 C	MURCEUTY PR 1.128. The Information is requir	ed to obtain or	naturn is bernefil by	the public which is to fit					

This collection of information is required by 25 U.S. . The collection is estimated to take 20 minutes to complete, including pashwing, preprint, and automotive from control considerable by 25 U.S. . CE2 and 37 CPR 1.1A This collection is estimated to take 20 minutes to fine you require to complete the form and/or expectation to the product of fine you require to complete the form and/or expectation to the considerable form and the supplement of the constant
Patent Atty, Dkt. No. APPM/006303/CPI/COPPER/PJS

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE BEFORE THE BOARD OF PATENT APPEALS AND INTERFERENCES

§

യയയയയയയയയ

In re Application of:

CHUNG, et al.

Serial No.: 09/965,370

Confirmation No.: 6507

Filed:

September 26, 2001

For:

INTEGRATION OF BARRIER LAYER AND

SEED LAYER

MAIL STOP APPEAL BRIEF-PATENTS Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

Dear Sir:

RECEIVED
CENTRAL FAX CENTER

Group Art Unit: 1762

JUL 3 1 2006

Examiner:

Eric B. Fuller

CERTIFICATE OF FACSIMILE TRANSMISSION UNDER 37 CFR 1.8

I hereby certify that this correspondence and the documents referred to as attached therein are being facsimile transmitted to the U.S. Patent and Trademark Office to the fax number indicated by the Examiner, namely, fax number (571) 273-8300 to the attention of the named Examiner, on the date below.

Date //31/00

7 F95 Cherr, 51,553

APPEAL BRIEF

Applicants submit this Appeal Brief to the Board of Patent Appeals and Interferences on appeal from the decision of the Examiner of Group Art Unit 1762 dated April 28, 2006, finally rejecting claims 1-7, 9-10, 39, 42, and 44-69. The final rejection of claims 1-7, 9-10, 39, 42, and 44-69 is appealed. This Appeal Brief is believed to be timely since mailed by the due date of July 31, 2006, as set by mailing a Notice of Appeal on May 30, 2006. Authorization to charge the fee of \$500.00 for filing this brief is provided on a separate fee transmittal. Please charge any additional fees that may be required to make this Appeal Brief timely and acceptable to Deposit Account No. 20-0782/APPM/006303/KMT.

08/02/2006 AWDNDAF1 00000009 501074 09965370

01 FC:1402

500.00 DA

BRIEF ON APPEAL Serial No. 09/965,370 Page 2 of 28

TABLE OF CONTENTS

1.	Identification Page	1
2.	Table of Contents	2
3.	Real Party in Interest	3
4.	Related Appeals and Interferences	4
5.	Status of Claims	5
6.	Status of Amendments	6
7.	Summary of Claimed Subject Matter	7
8.	Grounds of Rejection to be Reviewed on Appeal	10
9.	Arguments	11
10.	Conclusion	19
11.	Claims Appendix	20
12.	Evidence Appendix	27
13.	Related Proceedings Appendix	28

BRIEF ON APPEAL Serial No. 09/965,370 Page 3 of 28

Real Party in Interest

The present application has been assigned to Applied Materials, Inc., 3050 Bowers Avenue, Santa Clara, California 95054.

PEGEIVED CENTRAL FAX CENTER

JUL 3 1 2006

BRIEF ON APPEAL Serial No. 09/965,370 Page 4 of 28

Related Appeals and Interferences

Applicant asserts that no other appeals or interferences are known to the Applicant, the Applicant's legal representative, or assignee which will directly affect or be directly affected by or have a bearing on the Board's decision in the pending appeal.

BRIEF ON APPEAL Serial No. 09/965,370 Page 5 of 28

Status of Claims

Claims 1-7, 9-10, 39, 42, and 44-69 are pending in the application. Claims 1-69 were originally presented in the application. Claims 8, 11-38, 40-41, and 43 have been cancelled without prejudice.

Claims 1-7, 9-10, 39, 42, and 44-69 stand finally rejected as discussed below. The final rejection of claims 1-7, 9-10, 39, 42, and 44-69 is appealed.

PEGEIVED CENTRAL FAX CENTER JUL 3 1 2006

BRIEF ON APPEAL Serial No. 09/965,370 Page 6 of 28

Status of Amendments

All claim amendments have been entered by the Examiner. Amendments to the claims presented after the final rejection have been entered by the Examiner and included in the Claims Appendix.

BRIEF ON APPEAL Serial No. 09/965,370 Page 7 of 28

Summary of Claimed Subject Matter

Claimed embodiments of the invention provide a method of filling a feature. The method includes depositing a barrier layer, depositing a seed layer over the barrier layer, and depositing a conductive layer over the seed layer. In one aspect, the seed layer comprises a copper alloy seed layer deposited over the barrier layer. For example, the copper alloy seed layer may comprise copper and a metal, such as aluminum, magnesium, titanium, zirconium, tin, and combinations thereof. In another aspect, the seed layer comprises a copper alloy seed layer deposited over the barrier layer and a second seed layer deposited over the copper alloy seed layer. The copper alloy seed layer may comprise copper and a metal, such as aluminum, magnesium, titanium, zirconium, tin, and combinations thereof. The second seed layer may comprise a metal, such as undoped copper. In still another aspect, the seed layer comprises a first seed layer and a second seed layer. The first seed layer may comprise a metal, such as aluminum, magnesium, titanium, zirconium, tin, and combinations thereof. The second seed layer may comprise a metal, such as aluminum, magnesium, titanium, zirconium, tin, and combinations thereof. The second seed layer may comprise a metal, such as undoped copper. (See, Abstract)

In one embodiment, a copper alloy seed layer 502 is deposited over a barrier layer 204 and a copper conductive material layer 506 is deposited over the copper alloy seed layer 502 to fill the feature. (See, Figures 5A and paragraph 53.) In another embodiment, a copper alloy seed layer 512 is deposited over a barrier layer 204, a second seed layer 514 is deposited over the copper alloy seed layer 512, and a copper conductive material layer 516 is deposited over the second seed layer 514 to fill the feature. (See, Figure 5B and paragraph 54.) In another embodiment, a first seed layer 523 is deposited over a barrier layer 204, a second seed layer 524 is deposited over the first seed layer 523, and a copper conductive material layer 526 is deposited over the second seed layer 524 to fill the feature. (See, Figures 5C and paragraph 56.)

In the embodiments of independent claim 1, a method for filling a feature is provided, comprising depositing a barrier layer by atomic layer deposition (pages 6-7, paragraphs 27-29), the barrier layer having a thickness less than about 50 Å (page 10,

BRIEF ON APPEAL Serial No. 09/965,370 Page 8 of 28

paragraphs 31-36, and page 11, paragraph 42), depositing a seed layer over the barrier layer, the seed layer comprising copper and a metal selected from the group consisting of aluminum, magnesium, zirconium, and combinations thereof (page 13, paragraph 53 and page 17, paragraph 62), and then depositing a copper conductive material layer over the seed layer (page 13, paragraph 53, and page 16, paragraph 61).

In the embodiments of independent claim 39, a method of preparing a substrate structure for copper metallization is provided, comprising depositing a barrier layer by atomic layer deposition to a sidewall coverage of about 50 Å or less (pages 6-7, paragraphs 27-29, and page 11, paragraph 42), and then depositing a seed layer over the barrier layer, the seed layer comprising copper and a metal selected from the group consisting of aluminum, magnesium, zirconium, and combinations thereof (page 13, paragraph 53 and page 17, paragraph 62).

In the embodiments of independent claim 42, a method of filling a feature is provided, comprising depositing a barrier layer by atomic layer deposition, the barrier layer having a thickness of less than about 20 Å (pages 6-7, paragraphs 27-29), depositing a copper alloy seed layer over the barrier layer (page 13, paragraph 53 and page 17, paragraph 62), the copper alloy seed layer comprising copper and a metal in a concentration between about 0.01 atomic percent and 5.0 atomic percent (page 13, paragraph 53), the metal selected from the group consisting of aluminum, magnesium, zirconium, and combinations thereof (page 13, paragraph 53 and page 17, paragraph 62), and then depositing a copper conductive material layer over the copper alloy seed layer (page 13, paragraph 53, and page 16, paragraph 61).

In the embodiments of independent claim 47, a method of filling a feature is provided, comprising depositing a barrier layer by atomic layer deposition, the barrier layer having a thickness less than about 20 Å (pages 6-7, paragraphs 27-29), depositing a copper alloy seed layer over the barrier layer (page 14, paragraph 55), the copper alloy seed layer comprising copper and a metal in a concentration between about 0.01 atomic percent and 5.0 atomic percent (page 14 paragraph 55), the metal selected from the group consisting of aluminum, magnesium, zirconium, and

BRIEF ON APPEAL Serial No. 09/965,370 Page 9 of 28

combinations thereof (page 14, paragraph 55); depositing a second seed layer over the copper alloy seed layer (page 14, paragraph 55), and then depositing a copper conductive material layer over the second seed layer (page 14, paragraph 55, and page 16, paragraph 61).

In the embodiments of independent claim 53, a method of filling a feature is provided, comprising depositing a barrier layer by atomic layer deposition, the barrier layer having a thickness less than about 20 Å (pages 6-7, paragraphs 27-29), depositing a first seed layer over the barrier layer to a sidewall coverage between a submonolayer and about 50 Å (page 15, paragraphs 57-58), the first seed layer comprising aluminum (page 15, paragraph 57), depositing a second seed layer over the first seed layer (page 15, paragraph 57), and depositing a conductive material layer over the second seed layer (page 15, paragraph 57, and page 16, paragraph 61).

In the embodiments of independent claim 59, a method of preparing a substrate structure for electroplating of copper is provided, comprising depositing a barrier layer by atomic layer deposition, the barrier layer having a thickness less than about 20 Å (pages 6-7, paragraphs 27-29), and depositing a seed layer over the barrier layer, the seed layer comprising copper and aluminum (page 13, paragraph 53 and page 17, paragraph 62).

BRIEF ON APPEAL Serial No. 09/965,370 Page 10 of 28

Grounds of Rejection to be Reviewed on Appeal

- 1. Claims 1-7, 9-10, 39, 42, and 44-69 stand rejected under 35 USC § 103(a) as being obvious over *Lopatin et al.* (U.S. Patent No. 6,368,954) in view of *Lopatin et al.* (U.S. Patent No. 6,174,799).
- 2. Claims 42 and 44-69 stand rejected under 35 USC § 103(a) as being obvious over *Lopatin et al.* '954 in view of *Lopatin et al.* '799, and in further view of *Tsai et al.* (U.S. Patent No. 6,309,964).



JUL 3 1 2006

BRIEF ON APPEAL Serial No. 09/965,370 Page 11 of 28

ARGUMENTS

A. Rejection of Claims 1-7 and 9-10 over Lopatin et al.'954 in view of Lopatin et al. '799

Claims 1-7 and 9-10 stand rejected under 35 U.S.C. § 103(a) as being obvious over Lopatin et al. '954 in view of Lopatin et al. '799. The Examiner states that Lopatin et al. '954 teaches a barrier layer of 20-300 angstroms formed by atomic layer deposition and Lopatin et al. '799 teaches nitrogen grading in copper alloyed seed layers to increase adhesion to the barrier layer and decrease electro-migration. The Examiner states that it would have been obvious to use the constituents of the seed layer of Lopatin et al. '799 in the process of Lopatin et al. '954 to reap the benefits of the bulk copper layer having better adhesion to the barrier layer and decreased electro-migration.

Applicants have respectfully traversed the rejection based on the failure of Lopatin et al. '954 in view of Lopatin et al. '799 to teach or suggest all the limitations of the claimed subject matter. Lopatin et al. '954 teaches a barrier layer of 20-300 angstroms formed by atomic layer deposition (ALD), a pre-seed layer comprising copper formed by atomic layer epitaxy, and a seed layer comprising copper formed by chemical vapor deposition (CVD). Lopatin et al. '799 teaches a method depositing a seed layer over a barrier layer, the seed layer comprises a conductive metal material alloyed with a nitrided metal material, having a graded nitrogen content.

However, Lopatin et al. '954 in view of Lopatin et al. '799 does not teach, suggest, or motivate depositing of a seed layer, which comprises copper and a metal selected from the group consisting of aluminum, magnesium, zirconium, and combinations thereof, to be deposited over a thin barrier layer which is deposited by atomic layer deposition to a thickness of less than about 50 Å. The Examiner has failed to show a clear and particular motivation by the skilled artisan to select from the disclosures of Lopatin et al. '954 and Lopatin et al. '799. The only suggestion is provided in the Applicant's disclosure and thus hindsight.

BRIEF ON APPEAL Serial No. 09/965,370 Page 12 of 28

Applicant submits that "[t]he showing of a motivation to combine must be clear and particular, and it must be supported by actual evidence. In *re Dembiczak*, 50 U.S.P.Q. 2d 1614, 1617 (Fed. Cir. 1999). The Federal Circuit has also ruled that "[o]ne cannot use hindsight reconstruction to pick and choose among isolated disclosures in the prior art to deprecate the claimed invention." (In *re Fritch* at 1784). The only suggestion of the claimed subject matter is provided in the Applicant's disclosure, and thus the claims were rejected in hindsight.

Applicant asserts that a copper alloyed seed layer to be deposited over a thin ALD deposited barrier layer is not taught or suggested in the combination of *Lopatin et al.* '954 in view of *Lopatin et al.* '799. Accordingly, *Lopatin et al.* '954 in view of *Lopatin et al.* '799, alone or in combination, does not teach, show, or suggest depositing a barrier layer by atomic layer deposition, the barrier layer having a thickness less than about 50 Å, depositing a seed layer over the barrier layer, the seed layer comprising copper and a metal selected from the group consisting of aluminum, magnesium, zirconium, and combinations thereof, and then depositing a copper conductive material layer over the seed layer, as recited in claim 1 and claims dependent thereon. Withdrawal of the rejection is respectfully requested.

B. Rejection of Claim 39 over Lopatin et al. '799

Claim 39 stands rejected under 35 U.S.C. § 103(a) as being obvious over Lopatin et al. '954 in view of Lopatin et al. '799. Applicants have respectfully traversed the rejection based on the failure of Lopatin et al. '954 in view of Lopatin et al. '799 to teach or suggest all the limitations of claim 39.

Lopatin et al. '954 in view of Lopatin et al. '799 does not teach, suggest, or motivate depositing of a seed layer, which comprises copper and a metal selected from the group consisting of aluminum, magnesium, zirconium, and combinations thereof, to be deposited over a thin barrier layer which is deposited by atomic layer deposition to a sidewall coverage of about 50 Å or less. The Examiner has failed to show a clear and particular motivation by the skilled artisan to select from the disclosures of Lopatin et al. '799, in addition, Lopatin et al. '954 in view of Lopatin et al. '799,

BRIEF ON APPEAL Serial No. 09/965,370 Page 13 of 28

alone or in combination, does not teach, show, or suggest a barrier layer deposited to a sidewall coverage of about 50 Å or less.

Accordingly, Lopatin et al. '954 in view of Lopatin et al. '799, alone or in combination, does not teach, show, or suggest depositing a barrier layer by atomic layer deposition to a sidewall coverage of about 50 Å or less, and then depositing a seed layer over the barrier layer, the seed layer comprising copper and a metal selected from the group consisting of aluminum, magnesium, zirconium, and combinations thereof, as recited in claim 39. Withdrawal of the rejection is respectfully requested.

C. Rejection of Claims 42, 44-46 over Lopatin et al.'954 in view of Lopatin et al. '799

Claims 42, 44-46 stand rejected under 35 U.S.C. § 103(a) as being obvious over Lopatin et al. '954 in view of Lopatin et al. '799. Applicants have respectfully traversed the rejections based on failure of Lopatin et al. '954 in view of Lopatin et al. '799 to teach or suggest all the limitations of the claim 42 and claims dependent thereon.

Lopatin et al. '954 and Lopatin et al. '799 have been discussed above. In addition, Lopatin et al. '954 in view of Lopatin et al. '799, alone or in combination, does not teach, show, or suggest depositing a copper alloy seed layer comprising copper and a metal in a concentration between about 0.01 atomic percent and 5.0 atomic percent.

Accordingly, Lopatin et al. '954 in view of Lopatin et al. '799, alone or in combination, does not teach, show, or suggest depositing a barrier layer by atomic layer deposition, the barrier layer having a thickness of less than about 20 Å, depositing a copper alloy seed layer over the barrier layer, the copper alloy seed layer comprising copper and a metal in a concentration between about 0.01 atomic percent and 5.0 atomic percent, the metal selected from the group consisting of aluminum, magnesium, zirconium, and combinations thereof, and then depositing a copper conductive material layer over the copper alloy seed layer, as recited in claim 42 and claims dependent thereon. Withdrawal of the rejection is respectfully requested.

BRIEF ON APPEAL Serial No. 09/965,370 Page 14 of 28

D. Rejection of Claims 47-52 over Lopatin et al.'954 in view of Lopatin et al.'799

Claims 47-52 stand rejected under 35 USC § 103(a) as being obvious over Lopatin et al. '954 in view of Lopatin et al. '799. Applicants have respectfully traversed the rejections based on failure of Lopatin et al. '954 in view of Lopatin et al. '799 to teach or suggest all the limitations of the claim 47 and claims dependent thereon.

Lopatin et al. '954 and Lopatin et al. '799 have been discussed above. In addition, Lopatin et al. '954 in view of Lopatin et al. '799, alone or in combination, does not teach, show, or suggest a copper alloy seed layer comprising copper and a metal in a concentration between about 0.01 atomic percent and 5.0 atomic percent. Further, Lopatin et al. '954 in view of Lopatin et al. '799, alone or in combination, does not teach, show, or suggest a second copper seed layer to be deposited over a copper alloy seed layer comprising copper and a metal.

Accordingly, Lopatin et al. '954 in view of Lopatin et al. '799, alone or in combination, does not teach, show, or suggest depositing a barrier layer by atomic layer deposition, the barrier layer having a thickness less than about 20 Å, depositing a copper alloy seed layer over the barrier layer, the copper alloy seed layer comprising copper and a metal in a concentration between about 0.01 atomic percent and 5.0 atomic percent, the metal selected from the group consisting of aluminum, magnesium, zirconium, and combinations thereof, depositing a second seed layer over the copper alloy seed layer, and then depositing a copper conductive material layer over the second seed layer, as recited in claim 47 and claims dependent thereon. Withdrawal of the rejection is respectfully requested.

E. Rejection of Claims 53-58 over Lopatin et al.'954 in view of Lopatin et al.'799

Claims 53-58 stand rejected under 35 U.S.C. § 103(a) as being obvious over Lopatin et al. '954 in view of Lopatin et al. '799. Applicants have respectfully traversed the rejections based on failure of Lopatin et al. '954 in view of Lopatin et al. '799 to teach or suggest all the limitations of the claim 53 and claims dependent thereon.

BRIEF ON APPEAL Serial No. 09/965,370 Page 15 of 28

Lopatin et al. '954 and Lopatin et al. '799 have been discussed above. In addition, Lopatin et al. '954 in view of Lopatin et al. '799, alone or in combination, does not teach, show, or suggest a first seed layer comprising aluminum. Furthermore, Lopatin et al. '954 in view of Lopatin et al. '799, alone or in combination, does not teach, show, or suggest a second seed layer deposited over a first seed layer comprising aluminum. Still further, Lopatin et al. '954 in view of Lopatin et al. '799, alone or in combination, does not teach, show, or suggest a first aluminum seed layer deposited to a sidewall coverage between a sub-monolayer and about 50 Å to be deposited over a thin barrier layer having a thickness of less than about 20 Å.

Accordingly, Lopatin et al. '954 in view of Lopatin et al. '799, alone or in combination, does not teach, show, or suggest depositing a barrier layer by atomic layer deposition, the barrier layer having a thickness less than about 20 Å, depositing a first seed layer over the barrier layer to a sidewall coverage between a sub-monolayer and about 50 Å, the first seed layer comprising aluminum, depositing a second seed layer over the first seed layer, and depositing a conductive material layer over the second seed layer, as recited in claim 53 and claims dependent thereon. Withdrawal of the rejection is respectfully requested.

F. Rejection of Claims 59-69 over Lopatin et al.'954 in view of Lopatin et al. '799

Claims 59-69 stand rejected under 35 U.S.C. § 103(a) as being obvious over Lopatin et al. '954 in view of Lopatin et al. '799. Applicants have respectfully traversed the rejections based on failure of Lopatin et al. '954 in view of Lopatin et al. '799 to teach or suggest all the limitations of the claim 59 and claims dependent thereon.

Lopatin et al. '954 and Lopatin et al. '799 have been discussed above. In addition, Lopatin et al. '954 in view of Lopatin et al. '799, alone or in combination, does not teach, show, or suggest a seed layer comprising copper and aluminum to be deposited over a barrier layer deposited by ALD to a thickness of less than about 20 Å.

Accordingly, Lopatin et al. '954 in view of Lopatin et al. '799, alone or in combination, does not teach, show, or suggest depositing a barrier layer by atomic layer deposition, the barrier layer having a thickness less than about 20 Å, and depositing a

BRIEF ON APPEAL Serial No. 09/965,370 Page 18 of 28

seed layer over the barrier layer, the seed layer comprising copper and aluminum, as recited in claim 59 and claims dependent thereon. Withdrawal of the rejection is respectfully requested.

G. Rejection of Claims 42, 44-46 over Lopatin et al.'954 in view of Lopatin et al. '799, and in further view of Tsai et al.

Claims 42, 44-46 stand rejected under 35 U.S.C. § 103(a) as being obvious over Lopatin et al. '954 in view of Lopatin et al. '799, and in further view of Tsai et al. The Examiner states that Tsai et al. teaches a barrier layer being effective at a thickness of 10 angstroms and it would be obvious to use a thickness of 10 angstroms for the barrier layer as taught by an ALD process of Lopatin et al. '954. Applicants have respectfully traversed the rejections based on failure of Lopatin et al. '954 in view of Lopatin et al. '799, and in further view of Tsai et al. to teach or suggest all the limitations of the claim 42 and claims dependent thereon.

Tsai et al., as stated by the Examiner, discloses only a barrier layer of 10-500 angstroms. Combination of Tsai et al. with Lopatin et al. '954 and Lopatin et al. '799 does not disclose, suggest or motivate the subject matter as claimed in claims 42 and 44-69 or any element lacking in the combination of Lopatin et al. '954 and Lopatin et al. '799, as discussed above. For example, Tsai et al., does not disclose, suggest or motivate depositing a copper alloy seed layer comprising copper and a metal in a concentration between about 0.01 atomic percent and 5.0 atomic percent to be deposited over a barrier layer having a thickness of less than about 20 Å, as lacking in the combination of Lopatin et al. '954 and Lopatin et al. '799. Accordingly, withdrawal of the rejection is respectfully requested.

H. Rejection of Claims 47-52 over Lopatin et al. '954 In view of Lopatin et al. '799, and in further view of Tsai et al.

Claims 47-52 stand rejected under 35 U.S.C. § 103(a) as being obvious over Lopatin et al. '954 in view of Lopatin et al. '799, and in further view of Tsai et al. Applicants have respectfully traversed the rejections based on failure of Lopatin et al. '954 in view of Lopatin et al. '799, and in further view of Tsai et al. to teach or suggest all the limitations of the claim 47 and claims dependent thereon.

BRIEF ON APPEAL Serial No. 09/965,370 Page 17 of 28

Tsai et al. discloses only a barrier layer of 10-500 angstroms. Tsai et al. in combination with Lopatin et al. '954 and Lopatin et al. '799 does not disclose, suggest or motivate the subject matter as claimed in claims 47-52 or any element lacking in the combination of Lopatin et al. '954 and Lopatin et al. '799, as discussed above. For example, Tsai et al., does not disclose, suggest or motivate a metal in a concentration between about 0.01 atomic percent and 5.0 atomic percent to be deposited in a copper alloy seed layer comprising copper and the metal, as lacking in the combination of Lopatin et al. '954 and Lopatin et al. '799. In addition, Tsai et al., does not disclose, suggest or motivate a second copper seed layer deposited over a copper alloy seed layer comprising copper and a metal in a concentration between about 0.01 atomic percent and 5.0 atomic percent. Accordingly, withdrawal of the rejection is respectfully requested.

1. Rejection of Claims 53-58 over Lopatin et al.'954 in view of Lopatin et al. '799, and in further view of Tsai et al.

Claims 53-58 stand rejected under 35 U.S.C. § 103(a) as being obvious over Lopatin et al. '954 in view of Lopatin et al. '799, and in further view of Tsai et al. Applicants have respectfully traversed the rejections based on failure of Lopatin et al. '954 in view of Lopatin et al. '799, and in further view of Tsai et al. to teach or suggest all the limitations of the claim 53 and claims dependent thereon.

Tsai et al. discloses only a barrier layer of 10-500 angstroms. Tsai et al. in combination with Lopatin et al. '954 and Lopatin et al. '799 does not disclose, suggest or motivate the subject matter as claimed in claims 53-58 or any element lacking in the combination of Lopatin et al. '954 and Lopatin et al. '799, as discussed above. For example, Tsai et al., does not disclose, suggest or motivate a first seed layer comprising aluminum. In addition, Lopatin et al. '954 in view of Lopatin et al. '799, and in further view of Tsai et al., alone or in combination, does not teach, show, or suggest a second seed layer deposited over a first seed layer comprising aluminum. Further, Lopatin et al. '954 in view of Lopatin et al. '799, and in further view of Tsai et al., alone or in combination, does not teach, show, or suggest a first aluminum seed layer deposited to a sidewall coverage between a sub-monolayer and about 50 Å to be deposited over a

BRIEF ON APPEAL Serial No. 09/985,370 Page 18 of 28

thin barrier layer of a thickness of less than about 20 Å, as lacking in the combination of *Lopatin et al.* '954 and *Lopatin et al.* '799. Accordingly, withdrawal of the rejection is respectfully requested.

J. Rejection of Claims 59-69 over Lopatin et al.'954 in view of Lopatin et al.'799, and in further view of Tsai et al.

Claims 59-69 stand rejected under 35 U.S.C. § 103(a) as being obvious over Lopatin et al. '954 in view of Lopatin et al. '799, and in further view of Tsai et al. Applicants have respectfully traversed the rejections based on failure of Lopatin et al. '954 in view of Lopatin et al. '799, and in further view of Tsai et al. to teach or suggest all the limitations of the claim 59 and claims dependent thereon.

Tsai et al. discloses only a barrier layer of 10-500 angstroms. Tsai et al. in combination with Lopatin et al. '954 and Lopatin et al. '799 does not disclose, suggest or motivate the subject matter as claimed in claims 59-69 or any element lacking in the combination of Lopatin et al. '954 and Lopatin et al. '799, as discussed above. For example, Tsai et al., does not disclose, suggest or motivate a seed layer comprising copper and aluminum to be deposited over a thin barrier layer deposited by ALD to a thickness of less than about 20 Å, as lacking in the combination of Lopatin et al. '954 and Lopatin et al. '799. Accordingly, withdrawal of the rejection is respectfully requested.



JUL 3 1 2006

BRIEF ON APPEAL Serial No. 09/965,370 Page 19 of 28

CONCLUSION

The Examiner errs in finding that it would have been obvious to include a nitrogen graded copper alloyed seed layer as taught by *Lopatin et al.* '799 to be deposited over an ALD deposited barrier layer as disclosed by *Lopatin et al.* '954 to reject claims 1-7, 9-10, 39, 42, and 44-69 because *Lopatin et al.* '954 in view of *Lopatin et al.* '799, alone or in combination, does not teach, suggest, or motivate a seed layer comprising copper and a metal selected from the group consisting of aluminum, magnesium, zirconium, and combinations thereof to be deposited over a barrier layer, the barrier layer having a thickness less than about 50 Å and deposited by atomic layer deposition.

The Examiner further errs in finding that it would have been obvious to include a barrier layer at a thickness of 10 angstroms as taught by *Tsai et al.* to be combined in an ALD deposited barrier layer as disclosed by *Lopatin et al.* '954 in view of a nitrogen graded copper alloyed seed layer as taught by *Lopatin et al.* '799 to reject claims 42 and 44-69 because *Lopatin et al.* '954 in view of *Lopatin et al.* '799, and in further view of *Tsai et al.*, alone or in combination, does not teach, suggest, or motivate a copper alloy seed layer comprising copper and a metal in a concentration between about 0.01 atomic percent and 5.0 atomic percent, the metal selected from the group consisting of aluminum, magnesium, zirconium, and combinations thereof to be deposited over a barrier layer, the barrier layer having a thickness less than about 20 Å and deposited by atomic layer deposition.

Respectfully submitted,

Ya-Fen Chen

Registration No. 51,553

Patterson & Sheridan, L.L.P.

3040 Post Oak Blvd. Suite 1500

Houston, TX 77056

Telephone: (713) 623-4844 Facsimile: (713) 623-4846

Agent for Appellant(s)

BRIEF ON APPEAL Serial No. 09/965,370 Page 20 of 28

CLAIMS APPENDIX

1. (Previously Presented) A method of filling a feature, comprising:

depositing a barrier layer by atomic layer deposition, the barrier layer having a thickness less than about 50 Å;

depositing a seed layer over the barrier layer, the seed layer comprising copper and a metal selected from the group consisting of aluminum, magnesium, zirconium, and combinations thereof; and then

depositing a copper conductive material layer over the seed layer.

- 2. (Original) The method of claim 1, wherein the seed layer comprises a copper alloy seed layer of the copper and the metal.
- 3. (Original) The method of claim 1, wherein the seed layer comprises a first seed layer deposited over the barrier layer and a second seed layer deposited over the first seed layer.
- 4. (Original) The method of claim 3, wherein the first seed layer comprises a copper alloy seed layer of the copper and the metal.
- 5. (Original) The method of claim 4, wherein the second seed layer comprises undoped copper.
- 6. (Original) The method of claim 3, wherein the first seed layer comprises the metal.
- 7. (Original) The method of claim 6, wherein the second seed layer comprises undoped copper.
- 8. (Canceled)

BRIEF ON APPEAL Serial No. 09/965,370 Page 21 of 28

- 9. (Original) The method of claim 1, wherein the seed layer is deposited by a technique selected from the group consisting of physical vapor deposition, chemical vapor deposition, atomic layer deposition, electroless deposition, and combinations thereof.
- 10. (Original) The method of claim 1, wherein the copper conductive material layer is deposited by a technique selected from the group consisting of electroplating, electroless deposition, chemical vapor deposition, physical vapor deposition, and combinations thereof.

11-38. (Cancelled)

39. (Previously Presented) A method of preparing a substrate structure for copper metallization, comprising:

depositing a barrier layer by atomic layer deposition to a sidewall coverage of about 50 Å or less; and then

depositing a seed layer over the barrier layer, the seed layer comprising copper and a metal selected from the group consisting of aluminum, magnesium, zirconium, and combinations thereof.

40-41. (Cancelledi)

42. (Previously Presented) A method of filling a feature, comprising:

depositing a barrier layer by atomic layer deposition, the barrier layer having a thickness of less than about 20 Å;

depositing a copper alloy seed layer over the barrier layer, the copper alloy seed layer comprising copper and a metal in a concentration between about 0.01 atomic percent and 5.0 atomic percent, the metal selected from the group consisting of aluminum, magnesium, zirconium, and combinations thereof; and then

depositing a copper conductive material layer over the copper alloy seed layer.

BRIEF ON APPEAL Serial No. 09/965,370 Page 22 of 28

43. (Canceled)

- 44. (Original) The method of claim 42, wherein the barrier layer comprises a material selected from the group consisting of titanium, titanium nitride, titanium silicon nitride, tantalum, tantalum nitride, tantalum silicon nitride, tungsten, tungsten nitride, tungsten silicon nitride, and combinations thereof.
- 45. (Original) The method of claim 42, wherein the copper alloy seed layer is deposited by a technique selected from the group consisting of physical vapor deposition, chemical vapor deposition, atomic layer deposition, electroless deposition, and combinations thereof.
- 46. (Original) The method of claim 42, wherein the copper conductive material layer is deposited by a technique selected from the group consisting of electroplating, electroless deposition, chemical vapor deposition, physical vapor deposition, and combinations thereof.
- 47. (Previously Presented) A method of filling a feature, comprising:

depositing a barrier layer by atomic layer deposition, the barrier layer having a thickness less than about 20 Å;

depositing a copper alloy seed layer over the barrier layer, the copper alloy seed layer comprising copper and a metal in a concentration between about 0.01 atomic percent and 5.0 atomic percent, the metal selected from the group consisting of aluminum, magnesium, zirconium, and combinations thereof;

depositing a second seed layer over the copper alloy seed layer; and then depositing a copper conductive material layer over the second seed layer.

48. (Original) The method of claim 47, wherein the barrier layer comprises a material selected from the group consisting of titanium, titanium nitride, titanium silicon nitride, tantalum, tantalum nitride, tantalum silicon nitride, tungsten, tungsten nitride, tungsten silicon nitride, and combinations thereof.

- 49. (Original) The method of claim 47, wherein the second seed layer comprises undoped copper.
- 50. (Original) The method of claim 47, wherein the copper alloy seed layer is deposited by a technique selected from the group consisting of physical vapor deposition, chemical vapor deposition, atomic layer deposition, electroless deposition, and combinations thereof.
- 51. (Original) The method of claim 47, wherein the second seed layer is deposited by a technique selected from the group consisting of physical vapor deposition, chemical vapor deposition, atomic layer deposition, electroless deposition, and combinations thereof.
- 52. (Original) The method of claim 47, wherein the copper conductive material layer is deposited by a technique selected from the group consisting of electroplating, electroless deposition, chemical vapor deposition, physical vapor deposition, and combinations thereof.
- 53. (Previously Presented) A method of filling a feature, comprising:

 depositing a barrier layer by atomic layer deposition, the barrier layer having a

thickness less than about 20 Å;

depositing a first seed layer over the barrier layer to a sidewall coverage between a sub-monolayer and about 50 Å, the first seed layer comprising aluminum:

depositing a second seed layer over the first seed layer; and depositing a conductive material layer over the second seed layer.

54. (Original) The method of claim 53, wherein the barrier layer comprises a material selected from the group consisting of titanium, titanium nitride, titanium silicon nitride, tantalum, tantalum nitride, tantalum silicon nitride, tungsten, tungsten nitride, tungsten silicon nitride, and combinations thereof.

BRIEF ON APPEAL Serial No. 09/965,370 Page 24 of 28

- 55. (Original) The method of claim 53, wherein the second seed layer comprises undoped copper.
- 56. (Original) The method of claim 53, wherein the first seed layer is deposited by a technique selected from the group consisting of physical vapor deposition, chemical vapor deposition, atomic layer deposition, electroless deposition, and combinations thereof.
- 57. (Original) The method of claim 53, wherein the second seed layer is deposited by a technique selected from the group consisting of physical vapor deposition, chemical vapor deposition, atomic layer deposition, electroless deposition, and combinations thereof.
- 58. (Original) The method of claim 53, wherein the copper conductive material layer is deposited by a technique selected from the group consisting of electroplating, electroless deposition, chemical vapor deposition, physical vapor deposition, and combinations thereof.
- 59. (Previously Presented) A method of preparing a substrate structure for electroplating of copper, comprising:

depositing a barrier layer by atomic layer deposition, the barrier layer having a thickness less than about 20 Å; and

depositing a seed layer over the barrier layer, the seed layer comprising copper and aluminum.

60. (Original) The method of claim 59, wherein the seed layer comprises a copper alloy seed layer of the copper and the aluminum, the aluminum present in the copper alloy seed layer in a concentration between about 0.001 atomic percent and about 5.0 atomic percent.

BRIEF ON APPEAL Serial No. 09/965,370 Page 25 of 28

- 61. (Original) The method of claim 60, wherein the copper alloy seed layer comprises the aluminum in a concentration between about 0.01 atomic percent and about 2.0 atomic percent.
- 62. (Original) The method of claim 60, wherein the copper alloy seed layer comprises the aluminum in a concentration between about 0.1 atomic percent and about 1.0 atomic percent.
- 63. (Original) The method of claim 59, wherein the seed layer comprises a first seed layer deposited over the barrier layer and a second seed layer deposited over the first seed layer.
- 64. (Original) The method of claim 63, wherein the first seed layer comprises a copper alloy seed layer of the copper and the aluminum, the aluminum present in the copper alloy seed layer in a concentration between about 0.001 atomic percent and about 5.0 atomic percent and wherein the second seed layer comprises undoped copper.
- 65. (Original) The method of claim 64, wherein the copper alloy seed layer comprises the aluminum in a concentration between about 0.01 atomic percent and about 2.0 atomic percent.
- 66. (Original) The method of claim 64, wherein the copper alloy seed layer comprises the aluminum in a concentration between about 0.1 atomic percent and about 1.0 atomic percent.
- 67. (Original) The method of claim 63, wherein the first seed layer comprises aluminum to a sidewall coverage between a sub-monolayer and about 50 Å and wherein the second seed layer comprises undoped copper.

BRIEF ON APPEAL Serial No. 09/965,370 Page 28 of 28

- 68. (Original) The method of claim 59, wherein the barrier layer comprises a material selected from the group consisting of titanium, titanium nitride, titanium silicon nitride, tantalum, tantalum nitride, tantalum silicon nitride, tungsten, tungsten nitride, tungsten silicon nitride, and combinations thereof.
- 69. (Original)The method of claim 59, wherein the seed layer is deposited by a technique selected from the group consisting of physical vapor deposition, chemical vapor deposition, atomic layer deposition, electroless deposition, and combinations thereof.

BRIEF ON APPEAL Serial No. 09/965,370 Page 27 of 28

EVIDENCE APPENDIX

No evidence is submitted.

BRIEF ON APPEAL Serial No. 09/965,370 Page 28 of 28

RELATED PROCEEDINGS APPENDIX

No copies of decisions rendered by a court or the Board in the related appeal or interference listed on page 4 of this Brief are included as there have been no related appeal or interference listed on page 4 of this Brief.